

INCAS 45-90


Apparecchio da incasso fisso per illuminazione d'accento o diffusa mediante impiego di vetro diffusore satinato disponibile come accessorio. Per sorgente LED integrata o per lampade LED GU10 230V/240V. Alimentazione remota disponibile come accessorio per le sorgenti a LED integrate. Corpo e cornice di battuta metallo verniciato. Installabile, anche, in pareti e soffitti in calcestruzzo o laterizio mediante apposita cassaforma in lamiera zincata disponibile come accessorio. Grado di protezione IP20/IP23.

Fixed recessed luminaire for accent or diffused lighting by using satin diffuser glass available as an accessory. For integrated LED source or for GU10 LED lamps 230V/240V. Remote power supply available as an accessory for the integrated LED sources. Body and frame in painted metal. It can, also, be installed in concrete or brick ceilings using a special galvanized metal outercasing available as accessory. IP20/IP23.





INCAS 45



0.25 A++ IP20 CE


500 92X90

LED	W	mA	Dim.	lm product/beam	3000K	CODE	Col.
5	500		100x100x80	460	22°	IN45.930S	/01

QT-14 c G9 230V	W	Dim.	CODE	Col.
1x max 60		100x100x80	IN45G9	/01

Accessori - accessories: VT/IN45.90: vetro diffusore satinato incas 45/90 - frosted glass diffuser - CC94: cassaforma incas 90 - 45 - Wallbox incas 90 - 45

INCAS 90




500 92X90

LED	W	mA	Dim.	lm product/beam	3000K	CODE	Col.
5	500		100x100x80	460	22°	IN90.930S	/01

GU10 LED	W	Dim.	CODE	Col.
1x max 50		100x100x80	IN90GU	/01

Accessori - accessories: VT/IN45.90: vetro diffusore satinato incas 45/90 - frosted glass diffuser - CC94: cassaforma incas 90 - 45 - Wallbox incas 90 - 45

INCAS 45 MICRO



500 54X54


LED	W	mA	Dim.	lm product/beam	3000K	CODE	Col.
1,5	500		62x62x60	136	30°	IN93L2	/01

QT12-LPGY6,35 12V	W	Dim.	CODE	Col.
1x max 35		62x62x60	IN93	/01

Accessori - accessories: VT/IN92: vetro diffusore satinato incas 45/90 MICRO - frosted glass diffuser - CC94M: cassaforma incas 90 - 45 micro - wallbox incas 90 - 45 micro

Vetro diffusore satinato conferisce al prodotto grado di protezione IP40. | Frosted glass diffuser provides the fixture IP40 protection

INCAS 90 MICRO



500 54X54

LED	W	mA	Dim.	lm product/beam	3000K	CODE	Col.
1,5	500		62x62x65	136	30°	IN92L2	/01


QR-CB35 GU4 12V	W	Dim.	CODE	Col.
1x max 35		62x62x65	IN92	/01

Accessori - accessories: VT/IN92: vetro diffusore satinato incas 45/90 MICRO - frosted glass diffuser - CC94M: cassaforma incas 90 - 45 micro - wallbox incas 90 - 45 micro

Vetro diffusore satinato conferisce al prodotto grado di protezione IP40 | frosted glass diffuser provides the fixture IP40 protection





VETRO DIFFUSORE SATINATO
FROSTED GLASS DIFFUSER



		CODE
INCAS 45/90	81X84	VT/IN45.90
INCAS45/90 MICRO	46X47	VT/IN92

L'inserimento di questo accessorio eleva il grado di protezione dell'apparecchio ad IP40 e IP43 | the inclusion of this accessory raises the protection degree of the lamp to IP40 and IP43

CASSAFORMA
WALLBOX



		CODE
INCAS 45/90		CC94
INCAS 45/90 MICRO		CC94M

Cassaforma in lamiera zincata per installazione in laterizio o calcestruzzo - galvanized metal wallbox for installing in brick or reinforced concrete

