



GINEICO



GANZO RISTORANTE - FIRENZE - ITALIA
PROJECT: ARCH. MASSIMO MATERASSI



SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: showroom@gineico.com

WWW.GINEICOLIGHTING.COM.AU

LENTI CON ANELLO OPTIONAL LENSES WITH RING



	ø mm	Kg	CODE	Col.
LENTE SATINATA / SATINED LENS	55	0,01	L055S.A	/01
	85	0,02	L085S.A	/02



	ø mm	Kg	CODE	Col.
LENTE ELISSOIDALE / ELIPSOID LENS	55	0,01	L055E.A	/01
	85	0,02	L085E.A	/02



	ø mm	Kg	CODE	Col.
LENTE ASIMMETRICA / ASYMMETRIC LENS	55	0,01	L055A.A	/01
	85	0,02	L085A.A	/02




	ø mm	Kg	CODE	Col.
FILTRO NIDO D'APE / HONEY COMB LOUVER	55	0,01	L055R.A	/01
	85	0,02	L085R.A	/02



PRO-IN TRACK

PRO IN FOCUS 55B BINARIO TRACK PROJECTOR





GU10 LED

W	ø mm	H mm	CODE	Col.
1x max 50	55	125	PI001	/01 /02

Accessori - accessories: L055A.A: Anello ø55 + lente - lens with ring ø55

PRO IN FOCUS 90V BINARIO TRACK PROJECTOR



LED	W	ø mm	H mm	lm product/beam 3000K			CODE	Col.
				15°	24°	38°		
17	90	150	1930	1827	1905	PI003.9	● ● ● /01 /02	
24,3	90	150	2468	2356	2430	PI004.9		
32	90	150	3006	2885	2955	PI005.9		

- Kelvin
- Beam
- Dimmable (optional)
- 27** 2700K
- 30** 3000K
- 40** 4000K
- HC** Horticulture
- TW** Tunable white Dali *
- S** 15°
- F** 24°
- W** 38°
- D** Dali
- DFD** Imm. Taglio di Fase / Dimmable trailing/leading edge

* Note: Gli apparecchi con temperatura di colore variabile (Tunable White) vengono forniti comprensivi di alimentatore DALI | The devices with variable color temperature (Tunable White) are supplied with integrated DALI power supply.

Accessori - accessories: L085S.A: Anello ø85 + lente - lens with ring ø85

Adattatore compatibile con binari One Track (A.A.G. Stucchi) o Global Track pulse (Nordic Aluminium) | Track adaptor compatible with One track (A.A.A.G.Stucchi) or Global Track pulse (Nordic Aluminium)

FOCUS 90

