




LBS


SOFFITTO CEILING

CEFLA IMOLA

LUCE PERIMETRALE PERIMETRIC EMISSION



LUCE DIRETTA/DIFFUSA DIRECT/DIFFUSED EMISSION



VERSIONI DISPONIBILI/AVAILABLE VERSION

- **KELVIN** ○ **KELVIN**
- 27 2700K 30 3000K
- 30 3000K 40 4000K
- 40 4000K
- TW** Tunable white Dali

● DIMMABLE (OPTIONAL)

D Dali Touch & Dimm


SU RICHIESTA ON DEMAND


E Versione ad emergenza / Emergency version

D10 Dimmerabile 1-10V / Dimmable 1-10V


CA Sistema di controllo CASAMBI/ CASAMBI control system


/ ## FINITURA/FINISHING


 /01 bianco/white

 /02 nero/black

/ ## FINITURA PREMIUM /PREMIUM FINISHING

 /81 oro rosa shine/shine pink gold

 /82 bronzo/ bronze

 /83 ottone spazzolato/ brushed brass

COMPOSIZIONE CODICE: xxx.x ●●●/##

HOW TO CREATE THE CODE: **F1000.827SD/01**

CODE

F1000.8 ● ● ● /## — finishing


base code

kelvin

beam

dimmable

LBS SOFFITTO LUCE PERIMETRALE CEILING PERIMETRIC EMISSION




info : Da completare con alimentatore da installare remoto in scatola di derivazione | To be completed with power supply to be installed in a remote junctionbox.

LED W	Ø mm	lm product/3000K	CODE
48	735	5712	LB001.8 ●/##
69	1035	8159	LB002.8 ●/##
90	1335	10605	LB003.8 ●/##


Accessories LB102.9: spot - spot

LBS SOFFITTO LUCE DIRETTA/DIFFUSA CEILING MOUNTED DIRECT/DIFFUSED EMISSION



LED W	Ø mm	lm product/3000K	CODE
48	735	3358	LB021.8 ●●/##
96	1035	6717	LB022.8 ●●/##
168	1335	11754	LB023.8 ●●/##

LBS CURVA ESSE S-CURVE



info : Da completare con alimentatore da installare remoto in scatola di derivazione | To be completed with power supply to be installed in a remote junction box

Linea di luce - LED line		W	Dim.	Lmm	lm product/3000K	CODE
87	562	4990	10393	LB210.8 ●/##		

Accessori - Accessories LB102.9: spot - spot

ACCESSORI / ACCESSORIES



LBS SPOT SPOT PROJECTOR



VEDI | SEE PAGE P.99