


CODE COMPOSITION

1502_2 S _E_ WD	
<i>light colour</i>	
27	2700K
30	3000K
40	4000K
<i>lens</i>	
22	22°
50	50°
<i>finishing</i>	
WH	white
BL	black

example of code composition 1502 BL 2 S 22 E 30 WD

TECHNICAL FEATURES

<b>Code</b>	<b>1502</b>
<b>Type</b>	Projector +/- 360°
<b>Material</b>	Aluminum
<b>Finishing</b>	White - Black Custom RAL (on request)
<b>Weight</b>	0.75 Kg
<b>Mounting</b>	Ceiling
<b>IP rating</b>	IP40
<b>Insulation class</b>	III
<b>Control gear</b>	Constant current electronic driver, remote installation (not included)
<b>Cut out for plasterboard</b>	-
<b>Lamp type</b>	LED 500 mA
<b>Lamp wattage</b>	1 x 6W
<b>Luminous efficacy</b>	130 lm/W - 3000K
<b>Light distribution</b>	Beam 22° Beam 50° (on request)
<b>Fitting</b>	-
<b>Light colour</b>	White 3000K White 2700K   4000K (on request)
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	>80 >90 (on request)
<b>Emergency</b>	On request
<b>Energy efficiency class</b>	A++
<b>Note</b>	On request available dimmable PUSH or DALI, remote installation.



CODE COMPOSITION

1503_2 T _E_ ND	
<i>light colour</i>	
27	2700K
30	3000K
40	4000K
<i>lens</i>	
22	22°
50	50°
<i>finishing</i>	
WH	white
BL	black

example of code composition 1503 BL 2 T 22 E 30 ND

TECHNICAL FEATURES

<b>Code</b>	<b>1503</b>
<b>Type</b>	Projector +/- 360°
<b>Material</b>	Aluminum
<b>Finishing</b>	White   Black Custom RAL (on request)
<b>Weight</b>	0.75 Kg
<b>Mounting</b>	Track
<b>IP rating</b>	IP40
<b>Insulation class</b>	III
<b>Control gear</b>	Constant current electronic driver on board
<b>Cut out for plasterboard</b>	-
<b>Lamp type</b>	LED 500 mA
<b>Lamp wattage</b>	1 x 6W
<b>Luminous efficacy</b>	130 lm/W - 3000K
<b>Light distribution</b>	Beam 22° Beam 50° (on request)
<b>Fitting</b>	-
<b>Light colour</b>	White 3000K White 2700K   4000K (on request)
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	>80 >90 (on request)
<b>Emergency</b>	On request
<b>Energy efficiency class</b>	A++
<b>Note</b>	On request available dimmable PUSH or DALI.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1502	H8500.A	Constant current electronic driver. Remote installation	Suitable for n°3 code 1502 - 500 mA
	H8500.C	Constant current electronic driver. Remote installation	Suitable for n°1 code 1502 - 500 mA

