



model	dimensions				mount	light source	current
	length (A)	length (b)	width (c)	length (d)	spikes (units)	#5mm led	mA (max)
LT1	40mm	40mm	10mm	120mm	1	1	20
LT3	32mm	50mm	25mm	150mm	1	3	20
LT6	39mm	60mm	32mm	170mm	1	6	40
LT12	45mm	70mm	38mm	170mm	1	12	80
LT21	66mm	100mm	50mm	180mm	2	21	140
LT30	67mm	110mm	63mm	180mm	2	30	200

Note: 1 Amp = 1000 milliamps (mA).

Copper:

Solid copper will age individually overtime to a verdigris finish. A bluish-green coating usually of carbonate of copper that forms on copper, brass or bronze when exposed to air for long periods of time. Colour can change towards a red-brown depending on the chemistry of the environment the copper is exposed to.

Specifications:

Casing is made from solid Copper in matt finish. Materials:

Face and Back 'Chocolate' is made from weatherproof premium quality

acrylic acrylic

Power Source:

Low Voltage 12 V DC input

(regulated)

Weatherproof

Rating:

Mounting: Solid Copper Earth Spike(s) Pre wired:

Rear entry 900mm (length) weatherproof cable (20 gauge)

Warranty:

Light This Light That Weatherproof harness (18 gauge) with screw in plugs, or similar Cabling:

State of art: WNICHIA:5mm LED type:

Cool or Warm White and Lush. LED Colours:

Other custom order colours available,

Features:

Australian Owned Australian Made Extremely Low Voltage 12 volt, not dangerous

Up to 50,000 hours life Directional light efficiency Ambient light

Solid state technology

No fragile glass environment

Non corrosive materials

Ideal for coastal environments

No Maintenance

No globes to maintain No Ultraviolet radiation

No Infrared radiation

No UV to attract insects

Cool to touch Doesn't burn plants

Doesn't breakdown materials

No Mercury

Easy installation, easy to move

Portable

Choice of sizes

Weatherproof IP 68

2 year replacement warranty