


## IFERROSI FLOOR

500 IP54 LED > 90 CRI A++ CE

700


### DOPPIO PALO



| LED | W   | mA  | ø spots | Kg | lm product/beam 3000K | CODE   | Col.        |
|-----|-----|-----|---------|----|-----------------------|--------|-------------|
| 24° | 18  | 500 | 120     | 22 | 1483                  | IF01.9 | ● ● /46 /99 |
| 24° | 6,7 | 700 | 60      | 22 | 650                   |        |             |

- Kelvin 30 3000K 40 4000K
- Beam F 24°

### PALO H3300-120




500 IP54 LED > 90 CRI A++ CE

| LED | W   | mA  | ø spot | Kg   | lm product/beam 3000K | CODE   | Col.        |
|-----|-----|-----|--------|------|-----------------------|--------|-------------|
| 24° | 18  | 500 | 120    | 16,5 | 1483                  | IF02.9 | ● ● /46 /99 |
| 24° | 6,7 | 700 | 60     | 16   | 712                   |        |             |

- Kelvin 30 3000K 40 4000K
- Beam F 24°




### PALO H3300-60



IP54 LED > 90 CRI A++ CE

| LED | W   | mA  | ø spot | Kg | lm product/beam 3000K | CODE   | Col.        |
|-----|-----|-----|--------|----|-----------------------|--------|-------------|
| 38° | 6,7 | 700 | 60     | 16 | 712                   | IF03.9 | ● ● /46 /99 |
| 38° | 6,7 | 700 | 60     | 16 | 712                   |        |             |

- Kelvin 30 3000K 40 4000K
- Beam W 38°



# GINEICO

## PALO H3300-60+60



| LED      |        | W        |       | mA       | ø spots | Kg   | lm product/beam 3000K |        | CODE | Col.       |
|----------|--------|----------|-------|----------|---------|------|-----------------------|--------|------|------------|
| 24°      | 38°    | 700      | 700   | 60       | 16      | 1300 | 1424                  | IF04.9 | ● ●  | /46<br>/99 |
| ● Kelvin | ● Beam | 30 3000K | F 24° | 40 4000K | W 38°   |      |                       |        |      |            |

## PALO H1300-60







| LED      |        | W        |       | mA       | ø   | Kg  | lm product/beam 3000K |        | CODE | Col.       |
|----------|--------|----------|-------|----------|-----|-----|-----------------------|--------|------|------------|
| 38°      | 38°    | 6,7      | 700   | 60       | 2,6 | 712 |                       | IF05.9 | ● ●  | /99<br>/46 |
| ● Kelvin | ● Beam | 30 3000K | W 38° | 40 4000K |     |     |                       |        |      |            |

## PALO H700-36



| LED      |        | W        |       | mA       | ø spot | Kg  | lm product/beam 3000K |        | CODE | Col. |
|----------|--------|----------|-------|----------|--------|-----|-----------------------|--------|------|------|
| 19°      | 29°    | 8        | 700   | 36       | 0,5    | 665 | 695                   | IF06.9 | ● ●  | /62  |
| ● Kelvin | ● Beam | 30 3000K | S 19° | 40 4000K | F 29°  |     |                       |        |      |      |

Cavo in dotazione | Cable included



SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND  
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: [showroom@gineico.com](mailto:showroom@gineico.com)

[WWW.GINEICOLIGHTING.COM.AU](http://WWW.GINEICOLIGHTING.COM.AU)