


## IFERROSI WALL

### SPOT120




LED		lm product/beam 3000K			CODE		Col.		
W	mA	ø spot	H	Kg	21°	24°	39°		
18	500	120	75	1,3	1642	1483	1473	<b>IF20.9</b>	● ● /44 /99

● Kelvin	● Beam
<b>30</b> 3000K	<b>S</b> 21°
<b>40</b> 4000K	<b>F</b> 24°
	<b>W</b> 39°

Cavo in dotazione 3 m| 3m of cable included



### SPOT60




LED 48V		lm product/beam 3000K			CODE		Col.	
W	mA	ø spot	H	Kg	24°	38°		
6,7	700	60	200	0,3	650	712	<b>IF21.9</b>	● ● /44C /99

● Kelvin	● Beam
<b>30</b> 3000K	<b>F</b> 24°
<b>40</b> 4000K	<b>W</b> 38°

Cavo in dotazione 3 m| 3m of cable included



### SPOT120 + CBL




LED		lm product/beam 3000K			CODE		Col.		
W	mA	ø spot	H	Kg	21°	24°	39°		
18	500	120	700	1,7	1642	1483	1473	<b>IF30.9</b>	● ● /44C /99

● Kelvin	● Beam
<b>30</b> 3000K	<b>S</b> 21°
<b>40</b> 4000K	<b>F</b> 24°
	<b>W</b> 39°

Cavo in dotazione 3 m| 3m of cable included



### SPOT60 + CBL




LED 48V		lm product/beam 3000K			CODE		Col.	
W	mA	ø spot	H	Kg	24°	38°		
6,7	700	60	200	0,8	650	712	<b>IF31.9</b>	● ● /44C /99

● Kelvin	● Beam
<b>30</b> 3000K	<b>F</b> 24°
<b>40</b> 4000K	<b>W</b> 38°


Cavo in dotazione 3 m| 3m of cable included




IFERROSI 60 6,7W LED24°




IFERROSI 60 6,7W LED38°



IFERROSI 120 18W LED21°



IFERROSI 120 18W LED24°



IFERROSI 120 18W LED39°

