

PIXEL




OLTRE 1000 lm IN 35 mm DI INGOMBRO.

Pixel, il nuovo prodotto che si ispira alla famiglia Genius, caratterizzato da linee semplici e raffinate si integra perfettamente nelle superfici in cui viene installato. Lo spazio di installazione si riduce e anche il meccanismo si semplifica. Apparecchio da interni a scomparsa totale in AirCoral® per soffitti in laterizio o cartongesso. La manutenzione della sorgente Led si effettua agevolmente attraverso il foro di emissione luce. Con un diametro di soli 16 mm e un fascio puntuale e scenografico è in grado di creare giochi di luce d'effetto attraverso la sua semplicità tecnica.

MORE THAN 1000 lm IN A SPACE OF 35 mm.

Pixel, the new product inspired by the Genius family and characterized by simple and refined lines, fits perfectly into the surfaces where it is installed. The installation space is reduced and the mechanism is also simplified. Totally disappearing indoor luminaire in AirCoral® for brick or plasterboard ceilings. The LED source maintenance is easily carried out through the emission hole. With its only Ø 16 mm diameter and a punctual and scenographic beam, it's capable of creating impactful light effects through its technical simplicity.



CODE COMPOSITION

1007.AC 4 R _ E _ WD

light colour



27	2700K
30	3000K
40	4000K

lens

15	15°
25	25°
45	45°

example of code composition 1007.AC 4 R 25 E 30 WD

TECHNICAL FEATURES

Code	1007 XX
Type	Downlight 90° 
Material	AC: AirCoral®
Absorption capacity*	1.39 m²
Weight	-
Mounting	Ceiling recessed
IP rating	IP40
Insulation class	III
Control gear	Remote constant current driver (not included)
Cut out for plasterboard	150 x 150 mm
Lamp type	LED 700 mA  Vf: 11.5 VDC
Lamp wattage	1 x 8.5W
Luminous efficacy	1000 lm
Light distribution	Narrow beam 15° Beam 25° 45° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Light hole	Ø 16 mm
Voltage connection	By driver (optional)
CRI	90
Emergency	-
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1007.AC	H8700.E	Constant current electronic driver. Remote installation	Suitable for n°1 or n°3 code 1007.AC - 700 mA
	BR1007LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 120 mm (instructions on page 502)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²