



SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: showroom@gineico.com

WWW.GINEICOLIGHTING.COM.AU



Scent



SYDNEY – MELBOURNE – GOLD COAST – PERTH – AUCKLAND
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: showroom@gineico.com

WWW.GINEICOLIGHTING.COM.AU



Scent






Applique mono o biemissione a luce radente per installazione in esterni a parete, ideale per l'illuminazione di scale, ingressi, aree di circolazione, portici, tettoie, facciate architettoniche.




Single or double emission lamp with grazing light for wall mounted outdoor installation, ideal for the illumination of staircases, entrances, circulation areas, arcades, canopies, architectural facades.

Info

Materiali e finiture <i>Materials and finishings</i>	Corpo in alluminio anodizzato o verniciato, diffusori in vetro temperato	Anodized or varnished aluminum body, tempered glass diffusers
Installazione <i>Installation</i>	Superficie (parete) Temperatura di esercizio: -10 °C ~ +45 °C	Surface (wall) Working temperature: -10 °C ~ +45 °C
Collegamento elettrico <i>Electrical connection</i>	Collegamento in parallelo Fornito con cavo in neoprene da 20 cm	Parallel connection Provided with 20 cm neoprene cable
Sorgente luminosa <i>Light source</i>	Sorgente LED integrata Durata di vita dei LED (L80B10): 50000 ore Max 3 SDCM	Integrated LED source LED Lifetime (L80B10): 50000 hours Max 3 SDCM
Accessori non inclusi <i>Not included accessories</i>	Distanziale da parete (solo mod. DM1, DM2) Alim. elettronico (solo versioni 24 Vdc) Dimmer elettronico (solo versioni 24 Vdc)	Wall spacer (DM1, DM2 models only) Electronic driver (24 Vdc versions only) Electronic dimmer (24 Vdc versions only)
Personalizzazioni possibili <i>Customizations on request</i>	Altre temperature di colore Altre finiture su specifica RAL	Other LED CCTs Other finishings to RAL specification



IP65  A/A+/A++  0,47 kg 

Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DS1 <i>Scent DS1</i>	01 02 1 x 2 W (2,5 W)	2 2700K 137 lm	S 11°	A Aluminum anodized	R 230 Vac No Dim	0
		3 3000K 137 lm	M 23°	B White RAL 9003		
		4 4000K 147 lm	L 43°	J Black anodized		
		9 Blue 34 lm	W 11°x39°	R Corten		

IP65  A/A+/A++  0,47 kg 


Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DS1 <i>Scent DS1</i>	01 02 1 x 2 W (2W)	2 2700K 137 lm	S 11°	A Aluminum anodized	P 24 Vdc Supply Dim	0
		3 3000K 137 lm	M 23°	B White RAL 9003		
		4 4000K 147 lm	L 43°	J Black anodized		
		9 Blue 34 lm	W 11°x39°	R Corten		

Models




Scent DS1


Optics




Optic 11°



Optic 23°



Optic 43°






Optic 11°x39°

Driver	Fixture
AZPCSETN020200	6
AZPV024N025670	10
AZPV024N060200	25
AZPV024N060670	25
AZPV024N150670	65
AZPV024N240670	100




Il numero può diminuire a seconda della sezione del cavo e della distanza

The number may decrease depending on the cable section and distance

Scent


IP65  A/A+/A++  0,47 kg 

Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DS2 <i>Scent DS2</i>	02 02 2 x 2 W (4,5 W)	2 2700K 274 lm	S 2x11°	A Aluminum anodized	R 230 Vac No Dim	0
		3 3000K 274 lm	M 2x23°	B White RAL 9003		
		4 4000K 294 lm	L 2x43°	J Black anodized		
		9 Blue 68 lm	W 2x11°x39°	R Corten		

IP65  A/A+/A++  0,47 kg 


Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DS2 <i>Scent DS2</i>	02 02 2 x 2 W (4 W)	2 2700K 274 lm	S 2x11°	A Aluminum anodized	P 24 Vdc Supply Dim	0
		3 3000K 274 lm	M 2x23°	B White RAL 9003		
		4 4000K 294 lm	L 2x43°	J Black anodized		
		9 Blue 68 lm	W 2x11°x39°	R Corten		

Models




Scent DS2


Optics




Optic 2x11°



Optic 2x23°



Optic 2x43°






Optic 2x11°x39°




Driver	Fixture
AZPCSETN020200	3
AZPV024N025670	5
AZPV024N060200	12
AZPV024N060670	12
AZPV024N150670	32
AZPV024N240670	50

Il numero può diminuire a seconda della sezione del cavo e della distanza

The number may decrease depending on the cable section and distance


IP65  A/A+/A++  1,00 kg 

Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DM1 03 02 <i>Scent DM1</i>	3 x 2 W (6,5 W)	2 2700K 413 lm	S 11° M 22° L 40°	A Aluminum anodized	R 230 Vac No Dim	0
		3 3000K 413 lm		B White RAL 9003		
		4 4000K 442 lm		J Black anodized		
		9 Blue 102 lm		R Corten		

IP65  A/A+/A++  1,00 kg 


Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DM1 03 02 <i>Scent DM1</i>	3 x 2 W (5 W)	2 2700K 413 lm	S 11° M 22° L 40°	A Aluminum anodized	P 24 Vdc Supply Dim	0
		3 3000K 413 lm		B White RAL 9003		
		4 4000K 442 lm		J Black anodized		
		9 Blue 102 lm		R Corten		

Models




Scent DM1


Optics



Optic 11°



Optic 22°




Optic 40°

Driver	Fixture
AZPCSETN020200	2
AZPV024N025670	3
AZPV024N060200	8
AZPV024N060670	8
AZPV024N150670	20
AZPV024N240670	35

Il numero può diminuire a seconda della sezione del cavo e della distanza

The number may decrease depending on the cable section and distance

Accessories



FT SC ZS1 A0
Distanziale da parete Scent DM1-DM2 (anodizzato alluminio)
Wall spacer (aluminum anodized) for Scent DM1-DM2




FT SC ZS1 B0
Distanziale da parete Scent DM1-DM2 (bianco)
Wall spacer (white) for Scent DM1-DM2

FT SC ZS1 J0
Distanziale da parete Scent DM1-DM2 (anodizzato nero)
Wall spacer (aluminum black) for Scent DM1-DM2




FT SC ZS1 R0
Distanziale da parete Scent DM1-DM2 (corten)
Wall spacer (corten) for Scent DM1-DM2

Code
FT SC ZS1 A0
FT SC ZS1 B0
FT SC ZS1 J0
FT SC ZS1 R0

Scent


IP65  A/A+/A++  1,00 kg 

Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DM2 06 02 <i>Scent DM2</i>	6 x 2 W (13 W)	2 2700K 826 lm	S 2x11°	A Aluminum anodized	R 230 Vac No Dim	0
		3 3000K 826 lm	M 2x22°	B White RAL 9003		
		4 4000K 884 lm	L 2x40°	J Black anodized		
				R Corten		

IP65  A/A+/A++  1,00 kg 


Model	LED No. (Power)	CCT & Output	Optics	Finishing	Supply & Control	Variant
FT SC DM2 06 02 <i>Scent DM2</i>	6 x 2 W (13 W)	2 2700K 826 lm	S 2x11°	A Aluminum anodized	P 24 Vdc Supply Dim	0
		3 3000K 826 lm	M 2x22°	B White RAL 9003		
		4 4000K 884 lm	L 2x40°	J Black anodized		
				R Corten		

Models




Scent DM2


Optics



Optic 2x11°



Optic 2x22°




Optic 2x40°

Driver	Fixture
AZPCSETN020200	1
AZPV024N025670	2
AZPV024N060200	5
AZPV024N060670	5
AZPV024N150670	13
AZPV024N240670	20

Il numero può diminuire a seconda della sezione del cavo e della distanza

The number may decrease depending on the cable section and distance

Accessories



FT SC ZS1 Ao
Distanziale da parete Scent DM1-DM2 (anodizzato alluminio)
Wall spacer (aluminum anodized) for Scent DM1-DM2

FT SC ZS1 Bo
Distanziale da parete Scent DM1-DM2 (bianco)
Wall spacer (white) for Scent DM1-DM2

FT SC ZS1 Jo
Distanziale da parete Scent DM1-DM2 (anodizzato nero)
Wall spacer (aluminum black) for Scent DM1-DM2

FT SC ZS1 Ro
Distanziale da parete Scent DM1-DM2 (corten)
Wall spacer (corten) for Scent DM1-DM2

Code

FT SC ZS1 Ao
FT SC ZS1 Bo
FT SC ZS1 Jo
FT SC ZS1 Ro



SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: showroom@gineico.com

WWW.GINEICOLIGHTING.COM.AU

