



GINEICO

CHANDELIER




by Arianna e Bruno Teardo



USE

LED

FEATURES




Suspension lamp for indoor installations. Ideal in environments where indirect, diffused and relaxing light is required. It represents the modern and minimalist interpretation of the classic chandelier of the past. A true exaltation of crafts-manship, technology and design. The modularity of the structure makes it possible to create Chandeliers with dimensions larger than the standard ones. Structure in extruded aluminium alloy 6060/T6 with molded and laser-cut metal details. Diffuser made of opal polycarbonate, specific for Led, which combines maximum brightness with the ability to avoid Led effect. Steel support ropes, transparent PVC coated power cord. Equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Built-in electronic ballast. DM version equipped with dimmable ballast with DALI/PUSH interface. All electronic ballasts are equipped with thermal and short-circuit protection against overvoltage and overloading.

SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND
 G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA
 Phone: +61 417 950 455

Email: showroom@gineico.com
WWW.GINEICOLIGHTING.COM.AU



CHANDELIER 6




IP20

TYPE

POWER

FLUX*



LED

45W

4490lm

LED DM

45W

4490lm

CODE



CCT 3000°K
CRI>90

CCT 4000°K
CRI>90


L040 .W

L040 .N

L040 .WD

L040 .ND

CHANDELIER 6+3




IP20

TYPE

POWER

FLUX*



LED

60W

5990lm

LED DM

60W

5990lm

CCT 3000°K
CRI>90

CCT 4000°K
CRI>90


L041 .W

L041 .N

L041 .WD

L041 .ND

CHANDELIER 6+6




IP20

TYPE

POWER

FLUX*



LED

75W

7490lm

LED DM

75W

7490lm

CCT 3000°K
CRI>90

CCT 4000°K
CRI>90

L042 .W

L042 .N

L042 .WD

L042 .ND

