



Description

Adjustable indoor headlight suitable for wall or ceiling mounting, with body, rod and base in aluminium, available in three supply currents with remote power supply unit. Specific cooling fans design enables pushing high power/current in an extremely compact product package. Two rotation axes allow wide range in aiming


General specifications

tipo di installazione | *mounting type*
materiali | *materials*
finiture | *finishes*

a parete/soffitto | *wall/ceiling mounting*
alluminio | *aluminum*
bianco opaco RAL 9010, nero opaco RAL 9005, oro, extra mirror, custom | *matte white RAL 9010, matte black RAL 9005, gold, extra mirror, custom*

dimensioni | *overall dimensions*
peso | *weight*
grado di protezione IP | *IP rating*
note sul prodotto | *product notes*

Ø35x100mm
-
IP40
-



Electrical specifications

gruppo di alimentazione | *power supply unit*
alimentazione | *power supply*

non incluso | *non incluso*
corrente costante, 50/60Hz | *constant current, 50/60Hz*
11,2Vdc
su richiesta | *on demand*
III

tensione operativa LED | *LED operating voltage*
dimmerazione | *dimming*
classe di isolamento | *insulation class*

Light source

@ 4000K, Ta = 25°, Tj = 25°

lampada | *lamp*
temperatura di colore | *colour temperature*
indice di resa cromatica | *colour rendering index*
vita media | *average life*
consistenza cromatica | *colour consistency*

LED ad alta potenza | *high power LED*
2700 - 3000 - 4000K
≥90
50000h L80 B10
2 SDCM

I (mA)	Ø (lm)	P (W)	light efficiency (lm/W)
350	463	4	116
500	627	6	105
700	820	9	91

Optical group


schermo di chiusura | *lamp screen*
lente TIR | *TIR lens*

PMMA trasparente | *transparent PMMA*
policarbonato trasparente | *transparent polycarbonate*



Photometric data

apertura del fascio luminoso | *beam angle*



Accessories

alimentatore in CC 350mA 10W | *CC 350mA 10W driver*
alimentatore in CC 500mA 10W | *CC 500mA 10W driver*
alimentatore in CC 700mA 10W | *CC 700mA 10W driver*
alimentatore in CC 25W multicorrente dimmerabile | *25W dimmable CC multi-current driver*
DC-DC converter da CC a CV | *DC-DC converter CC to CV*
alimentatore in CV 60W 24V | *24V 60W CV driver*
nido d'ape | *honey comb*

Marchi e certificazioni | *Labels and certificates*

