



Description

Family of recessed and semi-recessed wall lamps, suitable for ambient illumination or as spotlight. It features a smooth and elliptical matrix, which develops around a little and simple light tube.

General specifications

tipo di installazione <i>mounting type</i>	Incasso <i>downlight</i>
materiali <i>materials</i>	alluminio, policarbonato <i>aluminum, polycarbonate</i>
finiture <i>finishes</i>	nero opaco RAL 9005, custom <i>matt black RAL 9005, custom</i>
dimensioni <i>overall dimensions</i>	55,5 x 55,5 x 30 mm
peso <i>weight</i>	80 gr
grado di protezione IP <i>IP rating</i>	IP40
fissaggio <i>Fixing</i>	molle
note sul prodotto <i>product notes</i>	-

Electrical specifications

gruppo di alimentazione <i>power supply unit</i>	non incluso <i>not included</i>
potenza <i>power</i>	2,5W
alimentazione <i>power supply</i>	10-30Vdc
assorbimento <i>absorption</i>	0,21A@12V/0,10A@24V
dimmerazione <i>dimming</i>	si <i>yes</i>
classe di isolamento <i>insulation class</i>	III

Light source

@ 4000K, Ta = 25°, Tj = 25°

lampada <i>lamp</i>	power LED
temperatura di colore <i>colour temperature</i>	3000 - 4000K
indice di resa cromatica <i>colour rendering index</i>	>90

Prodotto Product	Potenza Power	Flusso Luminoso Luminous Flux	Alimentazione Supply	CRI CRI	Angolo Angle	Temperatura Colore Color Temperature
Gea Frame 1 Spot	2,5W	110lm	350mA	95	100°	3000-4000K
Gea Frame 2 Spot	5W	220lm	350mA	95	100°	3000-4000K
Gea Frame 3 Spot	7,5W	330lm	350mA	95	100°	3000-4000K

Optical group

diffusore <i>diffuser</i>	policarbonato opalino <i>opal polycarbonate</i>
-----------------------------	---



SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: showroom@gineico.com
WWW.GINEICOLIGHTING.COM.AU

