



Description

Family of recessed and semi-recessed wall lamps, suitable for ambient illumination or as spotlight. It features a smooth and elliptical matrix, which develops around a little and simple light tube.

General specifications

| | |
|--|--|
| tipo di installazione <i>mounting type</i> | Incasso <i>downlight</i> |
| materiali <i>materials</i> | alluminio, policarbonato <i>aluminum, polycarbonate</i> |
| finiture <i>finishes</i> | nero opaco RAL 9005, custom <i>matt black RAL 9005, custom</i> |
| dimensioni <i>overall dimensions</i> | 114x44 mm |
| peso <i>weight</i> | 150 gr |
| grado di protezione IP <i>IP rating</i> | IP40 |
| fissaggio <i>Fixing</i> | molle |
| note sul prodotto <i>product notes</i> | - |

Electrical specifications

| | |
|--|-----------------------------------|
| gruppo di alimentazione <i>power supply unit</i> | non incluso <i>not included</i> |
| potenza <i>power</i> | 4,5W |
| alimentazione <i>power supply</i> | 9-32Vdc |
| assorbimento <i>absorption</i> | 0,37@12V/0,18@24V |
| dimmerazione <i>dimming</i> | si <i>yes</i> |
| classe di isolamento <i>insulation class</i> | III |

Light source

@ 4000K, Ta = 25°, Tj = 25°

| | |
|--|--------------|
| lampada <i>lamp</i> | power LED |
| temperatura di colore <i>colour temperature</i> | 3000 - 4000K |
| indice di resa cromatica <i>colour rendering index</i> | ≥ 90 |

| Prodotto Product | Potenza Power | Flusso Luminoso Luminous Flux | Alimentazione Supply | CRI CRI | Angolo Angle | Temperatura Colore Color Temperature |
|---------------------|------------------|----------------------------------|-------------------------|------------|-----------------|---|
| Gea Mini | 4,5W | 161lm | 10-30Vdc | ≥ 90 | 100° | 3000-4000K |

Optical group

| | |
|-----------------------------|---|
| diffusore <i>diffuser</i> | policarbonato opalino <i>opal polycarbonate</i> |
|-----------------------------|---|

