



Description

available in three photometric distributions and two powers with remote or included control gear.

General specifications

tipo di installazione <i>mounting type</i>	plafone <i>ceiling</i>
materiali <i>materials</i>	ferro, alluminio, nylon caricato <i>iron, aluminum, reinforced nylon</i>
finiture <i>finishes</i>	bianco opaco RAL 9010, nero opaco RAL 9005, oro, bronzo, rame, brunito, corten, ottone spazzolato, custom <i>matt white RAL 9010, matt black RAL 9005, gold, bronze, copper, burnished, corten, brushed brass, custom</i>
dimensioni <i>overall dimensions</i>	100x100x100mm (faretto), 100x100x100mm (headlight)
peso <i>weight</i>	980 gr.
grado di protezione IP <i>IP rating</i>	IP65

Electrical specifications

versione 220Vac | *220Vac version*

gruppo di alimentazione <i>power supply unit</i>	incluso <i>included</i>
alimentazione <i>power supply</i>	220Vac
dimmerazione <i>dimming</i>	non dimmerabile <i>not dimmable</i>
classe di isolamento <i>insulation class</i>	II

versione SELV | *SELV version*

gruppo di alimentazione <i>power supply unit</i>	non incluso <i>not included</i>
alimentazione <i>power supply</i>	24Vdc
dimmerazione <i>dimming</i>	su richiesta <i>on demand</i>
classe di isolamento <i>insulation class</i>	III

Light source

@ 4000K, Ta = 25°, Tj = 25°

lampada <i>lamp</i>	LED ad alta potenza <i>high power LED</i>
temperatura di colore <i>colour temperature</i>	2700 - 3000 - 4000K
indice di resa cromatica <i>colour rendering index</i>	≥90
vita media <i>average life</i>	50000h L80 B10
consistenza cromatica <i>colour consistency</i>	2 SDCM

Ø (lm)	P (W)	light efficiency (lm/W)
357	4	89
452	6	75

Optical group

schermo di chiusura <i>screen lamp</i>	polycarbonato trasparente <i>transparent polycarbonate</i>
lente TIR <i>TIR lens</i>	polycarbonato trasparente <i>transparent polycarbonate</i>

SYDNEY - MELBOURNE - GOLD COAST - PERTH - AUCKLAND
G45, 76-84 WATERWAY DRIVE COOMERA, QLD, 4209, AUSTRALIA

Phone: +61 417 950 455

Email: showroom@gineico.com

WWW.GINEICOLIGHTING.COM.AU

