



Description

Lighting fixture with ceiling/floor fixing for interiors. Consisting of an aluminum body and satin optical polymer diffuser. The LED source with 360° emission and high color rendering is oriented vertically. The height of the rod and the lamp body is defined based on the project and intended use. Fixing using masonry bushings.

General specifications

tipo di installazione <i>mounting type</i>	solaio/pavimento <i>ceiling/floor</i>
materiali <i>materials</i>	alluminio, PMMA <i>aluminum, PMMA</i>
finiture <i>finishes</i>	bianco opaco RAL 9010, nero opaco RAL 9005, oro, bronzo, rame, brunito, corten, ottone spazzolato, custom <i>matt white RAL 9010, matt black RAL 9005, gold, bronze, copper, burnished, corten, brushed brass, custom</i>
dimensioni <i>overall dimensions</i>	-
peso <i>weight</i>	-
grado di protezione IP <i>IP rating</i>	IP54

Electrical specifications

gruppo di alimentazione <i>power supply unit</i>	non incluso <i>not included</i>
potenza <i>power supply</i>	18W
alimentazione <i>power supply</i>	220-240Vdc, 50/60Hz <i>220-240Vdc, 50/60Hz</i>
dimmerazione <i>dimming</i>	su richiesta <i>on demand</i>
classe di isolamento <i>insulation class</i>	II

Light source

@ 4000K, Ta = 25°, Tj = 25°

lampada <i>lamp</i>	LED ad alta potenza <i>high power LED</i>
temperatura di colore <i>colour temperature</i>	2700 - 3000 - 4000K
indice di resa cromatica <i>colour rendering index</i>	≥90
vita media <i>average life</i>	35°C, 6000h
flusso luminoso <i>luminous flux</i>	1120lm

Optical group

diffusore <i>diffuser</i>	polycarbonato trasparente, PMMA parzialmente satinato <i>transparent polycarbonate, partly sandblasted PMMA</i>
-----------------------------	---

