



Description

selected accessory mounting kit it can be installed as pendant luminaire or on ceiling/wall surface and by the specific plastic clamps rotated around its longitudinal axis. It is available in three lengths, 1000/1500/2000mm.

General specifications

tipo di installazione <i>mounting type</i>	a sospensione, a parete o soffitto <i>pendant, on wall or ceiling</i>
materiali <i>materials</i>	alluminio, policarbonato <i>aluminum, polycarbonate</i>
finiture <i>finishes</i>	bianco opaco RAL 9010, nero opaco RAL 9005, pelle, custom <i>mat white RAL 9010, matt black RAL 9005, leather, custom</i>
dimensioni <i>overall dimensions</i>	Ø35x1000/1500/2000mm
peso <i>weight</i>	-
grado di protezione IP <i>IP rating</i>	IP20
note sul prodotto <i>product notes</i>	-

Electrical specifications

gruppo di alimentazione <i>power supply unit</i>	remote <i>remote</i>
tensione operativa LED <i>LED operating voltage</i>	220-240Vac, 50/60Hz
assorbimento <i>absorption</i>	24Vdc
dimmerazione <i>dimming</i>	su richiesta <i>on demand</i>
classe di isolamento <i>insulation class</i>	III

Light source

© 4000K, Ta = 25°, Tj = 25°

lampada <i>lamp</i>	linea LED ad alta luminosità <i>high luminosity LED line</i>
temperatura di colore <i>colour temperature</i>	2700 - 3000 - 4000K
indice di resa cromatica <i>colour rendering index</i>	≥90
vita media <i>average life</i>	50000h L80 B10
consistenza cromatica <i>colour consistency</i>	2 SDCM
efficienza luminosa <i>luminous efficiency</i>	42lm/W

L (mm)	Ø (lm)	P (W)
1000	1462	35
1500	2193	52
2000	2924	69

Optical group

diffusore <i>diffuser</i>	policarbonato opalino <i>opal polycarbonate</i>
-----------------------------	---