


## Scheda tecnica | Data sheet **LINEA S SPOT/UGR**

### Description

Mono and bi-emission suspension lighting system for indoor use with IP20 degree of protection, made of extruded aluminium, available in both spot and UGR optics versions, keeping the UGR level under 19. Perfect for offices and working spaces. Available lengths: 570 mm, 1130 mm or 1695 mm.


### General specifications

tipo di installazione   <i>mounting type</i>	sospensione   <i>suspension</i>
materiali   <i>materials</i>	alluminio, poliammide, policarbonato   <i>aluminum, polyamide, polycarbonate</i>
finiture   <i>finishes</i>	bianco opaco RAL 9016, nero opaco RAL 9005   <i>matt white RAL 9016, matt black RAL 9005</i>
peso   <i>weight</i>	-
grado di protezione IP   <i>IP rating</i>	IP20
lunghezze disponibili   <i>available length</i>	570 / 1130/1695 mm




### Electrical specifications

gruppo di alimentazione   <i>power supply unit</i>	non incluso   <i>not included</i>
alimentazione   <i>power supply</i>	tensione costante, 50/60Hz   <i>constant voltage, 50/60Hz</i>
tensione di alimentazione   <i>operating voltage</i>	48V
dimmerazione   <i>dimming</i>	su richiesta   <i>on demand</i>
classe di isolamento   <i>insulation class</i>	III



**Diffusore Spot**  
Spot diffuser



**Diffusore UGR**  
UGR diffuser

### Light source

© 3000K, Ta = 25°, Tj = 25°

lampada   <i>lamp</i>	LED ad alta potenza   <i>high power LED</i>
temperatura di colore   <i>colour temperature</i>	3000 - 4000K
indice di resa cromatica   <i>colour rendering index</i>	≥90
vita media   <i>average life</i>	50000h L90 B10
consistenza cromatica   <i>colour consistency</i>	-

Diffusore/Diffuser	Lunghezza/Length	P (W)	Ø (mm)	Fascio / Beam
Spot	570	12	1009	30°
Spot	1130	23	2017	30°
Spot	1695	33	3026	30°
UGR	570	12	1009	68°
UGR	1130	23	2017	68°
UGR	1695	33	3026	68°

