



Description

Recessed spotlight with overall dimensions $\varnothing 20\text{mm} \times h15\text{mm}$ and recess opening $\varnothing 12\text{mm}$. Power 0,5W. Suitable for indoor and outdoor wall, composed of PMMA sandblasted body. Protection degree IP66. 24V power supply is not included, it must be installed remotely.

General specifications

tipo di installazione <i>mounting type</i>	parete <i>wall</i>
materiali <i>materials</i>	PMMA
finiture <i>finishes</i>	sabbiato <i>sandblasted</i>
dimensioni <i>overall dimensions</i>	$\varnothing 20 \times 15\text{mm}$
peso <i>weight</i>	-
grado di protezione IP <i>IP rating</i>	IP66
grado di protezione IK <i>IK rating</i>	IK06
note sul prodotto <i>product notes</i>	-

Electrical specifications

gruppo di alimentazione <i>power supply unit</i>	non incluso <i>not included</i>
potenza <i>power</i>	0,5W
alimentazione <i>power supply</i>	10-30Vdc
assorbimento <i>absorption</i>	0,21A@12V/0,10A@24V
classe di isolamento <i>insulation class</i>	III

Light source

@ 4000K, $T_a = 25^\circ$, $T_j = 25^\circ$

lampada <i>lamp</i>	diode LED <i>LED diode</i>
temperatura di colore <i>colour temperature</i>	3000 - 4000K
indice di resa cromatica <i>colour rendering index</i>	≥ 90
vita media <i>average life</i>	50000h L80 B10
consistenza cromatica <i>colour consistency</i>	2 SDCM

\varnothing (lm)	P (W)	light efficiency (lm/W)
5	0,5	cortesia <i>courtesy</i>

Optical group

schermo di chiusura <i>lamp screen</i>	PMMA trasparente <i>transparent PMMA</i>
--	--

