

BEST



Apparecchi da incasso fisso o orientabile in pressofusione di alluminio verniciata, con sorgente LED integrata. Il modulo e' facilmente removibile senza l'utilizzo di attrezzi per agevolare il montaggio e l'eventuale manutenzione. Alimentatori disponibili come accessorio. Cornice di battuta disponibile bianca e nera. Grado di protezione IP20.

Recessed ceiling fixed and adjustable luminaires, made in die casted aluminum, painted by powder coating. Integrated LED source. The light engine can be removed without using any tool for an easy assemble and in case of maintenance. Power supplies available as accessories. The front trim is available in white and black. IP20.



MARCHIO DI PRODOTTO DEL REGNO UNITO CHE DEVE ESSERE UTILIZZATO PER I PRODOTTI IMMESSI SUL MERCATO IN GRAN BRETAGNA (INGHILTERRA, GALLES E SCOZIA) A DIMOSTRAZIONE DELLA CONFORMITÀ DEGLI STESSI ALLE NORMATIVE TECNICHE IN VIGORE IN UK. UK CONFORMITY ASSESSMENT AND EUROPEAN CERTIFICATION



PRODOTTI COSTRUITI CON MATERIALE RECICLABILE / PRODUCTS MADE OF RECYCLABLE MATERIAL



GARANZIA DI 5 ANNI / 5-YEAR WARRANTY



FISSO / FIXED



ORIENTABILE / ADJUSTABLE



DIAMETRO PRODOTTO / PRODUCT DIAMETER 65 mm - 83 mm - 105 mm



IDONEI PER CARTONGESSO OR LATERIZIO / CALCESTRUZZO a seconda dei modelli e degli accessori. SUITABLE FOR PLASTERBOARD OR BRICKWALL / CONCRETE it depends on the model and its accessories.

KELVIN

27		2700°K
30		3000°K
35		3500°K
40		4000°K

FASCIO / BEAM

S		SPOT
F		FLOOD
W		WIDE

FINITURE STANDARD / STANDARD FINISHINGS

/ 01		BIANCO / WHITE
/ 02		NERO / BLACK

BEST FRAME



VERSIONI DISPONIBILI / AVAILABLE VERSION

- **KELVIN**
- 27 2700K
- 30 3000K
- 35 3500K
- 40 4000K

- **FASCIO / BEAM**
- F Flood 24°
- W Wide 38°

- **PARABOLA / REFLECTOR**
- B Bianco / White
- N Nero / black
- L Lucido / Polished

- **DIMMABLE (OPTIONAL)**
- D Dali Touch & Dimm
- /## **FINITURA | FINISHING**
- /01 bianco | white
- /02 nero | black

COMPOSIZIONE CODICE: xxx.x ●●●/##
 HOW TO CREATE THE CODE: **F1000.827SX D / 01**
 CODE


F1000.8 ●●● /## finishing
 | kelvin | beam | reflector | dimmable
 base code

PARABOLA U / U REFLECTOR

- Wallwasher lucido / polished wallwasher

120 300 500 DRIVERS VEDI | SEE P.452

55 FISSO | FIXED




taglio per incasso / recessed hole dimension \varnothing 55
 NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED 120 IP20 5000h 50000lm 50000lm 50000lm 50000lm 50000lm

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
5	120	65	76	0,49	650	650			BT550.9 ●●● /##

WALLWASHER

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
5	120	65	76	0,49	650	650			BT550.9 ●●● /##


ORIENTABILE | ADJUSTABLE



LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
5	120	65	76	0,49	650	650			BT551.9 ●●● /##

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
5	120	65	76	0,49	650	650			BT551.9 ●●● /##

75 FISSO | FIXED




taglio per incasso / recessed hole dimension \varnothing 75
 NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED 300 IP20 5000h 50000lm 50000lm 50000lm 50000lm 50000lm

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
12	300	83	100	0,49	1560	1560			BT750.9 ●●● /##

WALLWASHER

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
12	300	83	100	0,49	1560	1560			BT750.9 ●●● /##


ORIENTABILE | ADJUSTABLE



LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
12	300	83	100	0,49	1560	1560			BT751.9 ●●● /##

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
12	300	83	100	0,49	1560	1560			BT751.9 ●●● /##

95 FISSO | FIXED




taglio per incasso / recessed hole dimension \varnothing 95
 NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED 500 IP20 5000h 50000lm 50000lm 50000lm 50000lm 50000lm

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
20	500	105	134	0,49	2600	2600			BT950.9 ●●● /##

WALLWASHER

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
20	500	105	134	0,49	2600	2600			BT950.9 ●●● /##

ORIENTABILE | ADJUSTABLE



LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
20	500	105	134	0,49	2600	2600			BT951.9 ●●● /##

LED	W	mA	ø	H	Kg	lm product / beam 3000K	F24°	W38°	CODE
20	500	105	134	0,49	2600	2600			BT951.9 ●●● /##

BEST

MINIMAL



VERSIONI DISPONIBILI / AVAILABLE VERSION

- **KELVIN**
- **FASCIO / BEAM**
- 2700K
- 3000K
- 3500K
- 4000K
- **F** Flood 24°
- **W** Wide 38°

- **PARABOLA / REFLECTOR**
- **B** Bianco / White
- **N** Nero / black
- **L** Lucido / Polished

- **DIMMABLE (OPTIONAL)**
- **D** Dali Touch & Dimm
- ## FINITURA | FINISHING**
- /01 bianco | white
- /02 nero | black

COMPOSIZIONE CODICE: xxx.x ●●●● /

HOW TO CREATE THE CODE: **F1000.827SXU / 01**
CODE


F1000.8 ●●●● / ## finishing
base code | kelvin | beam | reflector | dimmable

PARABOLA U / U REFLECTOR


- Wallwasher lucido / polished wallwasher

120 300 500 DRIVERS VEDI | SEE P.452


55 FISSO | FIXED




ORIENTABILE | ADJUSTABLE




75 FISSO | FIXED




ORIENTABILE | ADJUSTABLE



95 FISSO | FIXED



ORIENTABILE | ADJUSTABLE



taglio per incasso / recessed hole dimension \varnothing 55

NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED **120**

LED W	mA	ø	H	Kg	lm product/beam 3000K F24° W38°	CODE
5	120	65	76	0,49	650 650	BT552.9 ●●●● / ##

WALLWASHER

LED W	mA	ø	H	Kg	lm product/beam 3000K F24° W38°	CODE
5	120	76	0,49	650 650	BT552.9 ●●●● / ##	

taglio per incasso / recessed hole dimension \varnothing 75

NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED **300**

LED W	mA	ø	H	Kg	lm product/beam 3000K F24° W38°	CODE
12	300	83	100	0,49	1560 1560	BT752.9 ●●●● / ##

WALLWASHER

LED W	mA	ø	H	Kg	lm product/beam 3000K F24° W38°	CODE
12	300	83	100	0,49	1560 1560	BT752.9 ●●●● / ##

taglio per incasso / recessed hole dimension \varnothing 95

NOTE: COMPLETARE CON DRIVER | DRIVER NOT INCLUDED **500**

LED W	mA	ø	H	Kg	lm product/beam 3000K F24° W38°	CODE
20	500	105	134	0,49	2600 2600	BT752.9 ●●●● / ##

WALLWASHER

LED W	mA	ø	H	Kg	lm product/beam 3000K F24° W38°	CODE
20	500	105	134	0,49	2600 2600	BT752.9 ●●●● / ##