


PIPEDINO

LAMPADA A PARETE LUCE DIRETTA,
INDIRETTA O A BIEMISSIONE

WALL LAMP, DIRECT,
INDIRECT OR BI-EMISSION LIGHT






Pipedino Open



OTHER AVAILABLE CODES

| | | |
|------------|---------------------|---------------------|
| 2926.27.AC | <i>lens</i> | 120° |
| | <i>light colour</i> | 2700K |
| 2926.40.AC | <i>lens</i> | 120° |
| | <i>light colour</i> | 4000K (on request). |

TECHNICAL FEATURES

| Code | 2926.AC | 2921.AC | 2922.AC |
|-------------------------|---|---|--|
| Type | Wall lamp | Wall lamp | Wall lamp |
| Material | AC: AirCoral® | AC: AirCoral® | AC: AirCoral® |
| Absorption capacity* | 5.09 m² | 5.09 m² | 5.09 m² |
| Mounting | Wall mounting | Wall mounting | Wall mounting |
| IP rating | IP20 | IP20 | IP20 |
| Insulation class | I | I | I |
| Control gear | Dimmable constant current driver (included) | - | - |
| Lamp type | LED 500 mA  | A 60  | QT-DE12 (75 mm)  |
| Lamp wattage | 2 × 6.5W | 1 × 100W max | 1 × 150W max |
| Luminous efficacy | 2 × 930 lm - 3000K | - | - |
| Light distribution | Wide beam 120° | - | - |
| Fitting | - | E27 | R7s |
| Light colour | White 3000K | - | - |
| Voltage connection | 220-240V · 50/60Hz | 220-240V · 50/60Hz | 220-240V · 50/60Hz |
| CRI | >90 | - | - |
| Emergency | - | - | - |
| Energy efficiency class | A+ | A+ | A |
| Note | Trailing-edge and leading-edge dimming (20 - 100%). Satin glass included. Other available light colours: 2700K, 4000K (on request). | - | - |

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²