



Pipedo



OTHER AVAILABLE CODES

2908.27.AC	lens light colour	120° 2700K
------------	----------------------	---------------

TECHNICAL FEATURES

	2908.AC Wall lamp	2901.AC Wall lamp	2902.AC Wall lamp
Code	2908.AC	2901.AC	2902.AC
Type	Wall lamp	Wall lamp	Wall lamp
Material	AC: AirCoraf	AC: AirCoraf	AC: AirCoraf
Absorption capacity*	13.31 m <sup>2</sup>	13.31 m <sup>2</sup>	13.31 m <sup>2</sup>
Mounting	Wall mounting	Wall mounting	Wall mounting
IP rating	IP20	IP20	IP20
Insulation class	I	I	I
Control gear	Dimmable constant current driver (included)	-	-
Lamp type	LED 500 mA 	A 60 	QT-DE12 (115 mm) 
Lamp wattage	1 x 12W	1 x 100W max	1 x 150W max
Luminous efficacy	1 x 1340 lm - 3000K	-	-
Light distribution	Wide beam 120°	-	-
Fitting	-	E27	R7s
Light colour	White 3000K	-	-
Voltage connection	220-240V •50/60Hz	220-240V •50/60Hz	220-240V •50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A+	A+	A
Note	Trailing-edge and leading-edge dimming (20 - 100%).  Satin glass included.  Other available light colours: 2700K, 4000K (on request).	-	-

\* The absorption capacity per m<sup>2</sup> calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m<sup>2</sup>